

Bona Classicseal Waterborne Hardwood Floor Sealer 1 gal

ClassicSeal wood floor sealer is specially formulated for use with Bona Naturale, Bona Traffic, Bona Mega, and Bona Strong finishes. Bonaseal seals the wood, minimizes grain raise, provides a build layer, and prevents the finish from penetrating into the wood surface.

Rating: Not Rated Yet

Price

Sales price \$63.75

Tax amount

[Ask a question about this product](#)

Manufacturer [Bona](#)

Description

Bona ClassicSeal Waterborne Hardwood Floor Sealer is a specially formulated waterborne sealer for use with all Bona waterborne finishes (Bona Naturale, Bona Traffic, Bona Mega, and Bona Strong). The exceptionally clear formula highlights the natural color of the wood, minimizes grain raise and tannin bleed, provides a build layer, and prevents the finish from penetrating into the wood surface. Virtually odorless and nonflammable.

see **ClassicSeal Hardwood Floor Sealer** [technical data sheet](#)

manufacturer part# WB200018005

gtin 00737025805005

packaging: 1 gal plastic bottle

Benefits:

- Seals the wood, preventing the finish from penetrating
- Minimizes tannin bleed, especially on white oak
- Reduces tendency for sidebonding
- Improves flow and leveling of finish coats
- Non-yellowing
- Fast drying 2-3 hours
- Virtually odorless
- Water clean-up
- GREENGUARD certified for indoor air quality

TECHNICAL DATA

Physical characteristics:

- Ingredients: Water, acrylic resin, dipropylene glycol monomethyl ether, defoamers.
- Color: Milky white (wet)

- pH: 7.8
- Solids: 36%
- Density: 8.70 lbs/gallon (1.04 S.G.)
- US Regulatory VOC: 100 g/L
- Gloss Level: N/A
- Odor: Non-offending

Application characteristics:

- Clarity: Clear when dry
- Leveling: Excellent
- Defoaming: Excellent
- Drying Time: approximately 2-3 hours (high humidity and/or low temperature conditions will extend the drying time)
- Coverage: 500-600 square feet per gallon
- Percent Cured After 24 Hours: N/A
- Maximum Cure: 100% after 1 week

Recommended use:

- Residential wood floors
- Commercial wood floors
- For use on newly sanded wood floors