Bona Woodline Polyurethane Wood Floor Finish Gloss 1 qt

Bona Woodline Polyurethane is a premium, low VOC, oil-modified wood floor finish for interior use on residential and commercial wood floors.

Rating: Not Rated Yet **Price**Sales price \$12.75

Tax amount

Ask a question about this product

Manufacturer Bona

Description

Bona Woodline Polyurethane Gloss is a premium, oil-modified wood floor finish formulated for interior use on residential and commercial wood floors. Provides a tough, protective coat. Slight amber color - enhances natural color of wood. VOC compliant in most areas.

see Bona Woodline Polyurethane technical data sheet

manufacturer part# ST750051058 packaging: 1 qt metal can

Key benefits:

- Provides a tough, protective coat
- Slight amber color enhances natural color of wood
- Does not require thinning under normal environmental and application conditions (65°-75°F, 40-60% relative humidity)
- Self-leveling
- Will adhere to most solvent-based stains and finishes and most waterborne finishes after proper preparation, drying times and curing times

Physical characteristics:

- Ingredients
- Satin and Semi-Gloss: Oil-modified polyurethane resin, mineral spirits (solvent), driers, silica
- Gloss: Oil-modified polyurethane resin, mineral spirits (solvent), alkyd resin, driers
- Color: Gold amber
- Solids: 43.5%
- Density: Gloss: 7.3 lbs/gallon (.87 S.G.); Satin and Semi-Gloss: 7.8 lbs./gallon (.94 S.G.)
- US Regulatory VOC: 510 g/L
- Gloss Level: Gloss: (60°) >90°; Semi-Gloss: 60; Satin: 30
- Odor: Mineral spirits
- Stability: One year shelf life in unopened container
- Flash Point: Satin and Semi-Gloss: 103° F (39°C); Gloss: 110° F (43°C)

• Packaging: 5 gallon pail, 1 gallon can, 1 quart can

- Application characteristics:
 Clarity: Gloss: Clear; Satin and Semi-Gloss: Slightly opaque
- Coverage: 500 square feet per gallon Percent Cured After 24 Hours: 40%
- Maximum Cure: 100% after 2 weeks
- Application Tools: Bona Brush, lambswool applicator
- Leveling: Good Defoaming: Excellent • Drying Time: 8-12 hours

Recommended use:

- Residential
- Commercial
- Not recommended over white or pastel stains