DuraSeal Quick Coat Penetrating Finish 112 Golden Oak Hardwood Flooring Stain 1 qt

DuraSeal Quick Coat Penetrating Finish (112 golden oak sheen) is a semi-transparent stain formulated to seal, color and provide exceptional durability when used on bare wood and masonry surfaces. This rich blend of oil and resin gives hardwood floors a soft, satiny sheen.

Rating: Not Rated Yet
Price
Sales price $19.75

Tax amount

Ask a question about this product

ManufacturerDuraSeal

Description

DuraSeal Quick Coat Penetrating Finish 112 Golden Oak Hardwood Flooring Stain is a semi-transparent stain formulated to seal, color and provide exceptional durability when used on bare wood and masonry surfaces. This rich blend of oil and resin gives hardwood floors a soft, satiny sheen. Its unique formulation provides a surface that can be topcoated in two hours. DuraSeal Quick Coat Penetrating Finish is available in existing DuraSeal colors as well as many **Certified Minwax colors** (click to explore Minwax stains). It can be used with or without a finish coat, and is compatible with all DuraSeal water-borne and oil-modified finish systems.

see DuraSeal Quick Coat technical data sheet
see DuraSeal Quick Coat color chart
manufacturer part# 861120000
packaging: 1 qt metal can

PRODUCT PROPERTIES:
• Dry time and cure: approximately 2-3 hours; note - dry time is based on conditions of 77? and 50% relative humidity.
• Coverage: first coat - approximately 500 sq.ft. per gallon; optional second coat - approximately 800 sq.ft. per gallon.
• Clean up: application tools should be cleaned with mineral spirits or paint thinner immediately after use.
• Solvent: non-photochemically reactive.
• Maintenance:
- Regularly remove dust and dirt by sweeping or vacuuming; periodic buffing will renew luster.
- Exceptionally worn areas may require an additional finish coat. Maintain floors sealed only with DuraSeal Quick Coat
• Penetrating Finish with DuraSeal Renovator Cleaner and Reconditioner.
• Storage: Store at room temperature. If stored at high temperature, cool to room temperature before use. Keep from freezing.

PHYSICAL PROPERTIES: (Typical ranges)
• Density: 6.9-7.5 lbs/gal
• Viscosity: 22-65 centipoise
• % Solids: 33-42%
• VOC: 550 grams/liter or 4.6 lbs/gal maximum