

Glitsa Wood Flour Cement 1 gal

Glitsa Wood Flour Cement is designed to be mixed with fine edger dust to make crack filler to match the color of the floor being filled. Wood Flour Cement will accept stain, as does the wood, and is fast drying.

Rating: Not Rated Yet

Price

[Ask a question about this product](#)

Manufacturer [Glitsa](#)

Description

Glitsa Wood Flour Cement is designed to be mixed with fine edger dust to make crack filler to match the color of the floor being filled. Wood Flour Cement will accept stain, as does the wood, and is fast drying.

Prior to use, turn off all pilot lights, air conditioners, heaters, and all other ignition sources. Since vapors may travel, prevent build up by ventilating areas of the job not being treated.

Always use fine edger dust (100 grit or finer). Use red oak dust for oak floors, teak dust for teak floors, etc. After the initial (or rough) sanding, mix Wood Flour Cement and the fine dust in a clean container. Stir until well blended. Keep adding Wood Flour Cement until the mixture becomes a trowelable consistency.

Wood Flour Cement filler will dry very hard. It has good adhesion to the edges of the floorboards and it will also accept stain. Unused mixed filler may be stored in a non-porous sealed container. Clean tools with lacquer thinner.

view Glitsa Wood Flour Cement [spec sheet file](#)
packaging: 1 US gallon metal can