

## Mapei Kerabond White Mortar 50 lbs

Mapei Kerabond White is a premium floor and wall dry-set mortar for interior and exterior applications.

Rating: Not Rated Yet

**Price**

Sales price \$23.96

Tax amount

[Ask a question about this product](#)

Manufacturer [Mapei](#)

Description

**Mapei Kerabond White Mortar** see [technical data sheet](#)

**Mapei Kerabond White** is a premium-grade, dry-set mortar for use in interior/exterior residential and commercial floor and wall applications when mixed with water.

gtin 093994102508

manufacturer part# 0010050

packaging: paper bag of 50 lbs. (22,7 kg)

color: white

**available also in** [gray color](#)

**Features and benefits:**

- For tile and stone on floors and walls
- Great for most substrates, tile and stone when mixed with Keralastic

**Where to use:**

- Most interior/exterior residential and commercial installations on floors and walls
- Installation of most ceramic tile, quarry tile, pavers and Saltillo tile
- To set cement backer units (CBUs), see manufacturer's installation guidelines.

**Limitations:**

- Install only at temperatures between 40°F and 95°F (4°C and 35°C).
- Do not use for moisture-sensitive stone (green marble, some limestone and granite), agglomerate tiles, cultured marble or resin-backed tiles. Instead, use suitable epoxy or urethane adhesives (see respective Technical Data Sheet for more information).
- Use a white mortar when installing light-colored stones and translucent marble.
- Do not use over dimensionally unstable substrates such as hardwood flooring, oriented strand board (OSB), substrates containing asbestos,

or metal. See “Suitable Substrates” section below.

- Do not use for installations subject to prolonged water immersion.
- Not recommended for areas subject to severe freeze/thaw conditions. Instead, use a liquid latex additive mortar system.

**Suitable Substrates:**

- Concrete (cured at least 28 days)
- Masonry cement block, brick, cement mortar beds and leveling coats

**Protection:**

- Protect from traffic for 24 hours. Protect from heavy traffic for 7 days.
- Protect from rain for 7 days.