

## Mapei Mapesil T Caulk

• manufacturer part# 01591 • gtin 093994015914

Rating: Not Rated Yet

### Price

Sales price \$15.23

Tax amount

[Ask a question about this product](#)

Manufacturer [Mapei](#)

### Description

**Mapei Mapesil T** is a professional-grade, 100%-silicone sealant for use on multiple substrates. This product is specifically formulated for heavy traffic and expansion/movement joints exceeding both ASTM and ANSI standards.

**Mapei Mapesil T caulk** see [technical data sheet](#)

manufacturer part# 01591

color: #15 bone

packaging 10.1 U.S. oz. (299 mL) cartridge

click for [Mapei Mapesil T caulk color palette](#)

### Features and benefits:

- Color-matched to MAPEI's color palette
- Formulated to a low sheen to match the gloss of grout joints
- Rated for heavy-traffic and expansion/movement joints
- 100% silicone for use in interior, exterior, wet and dry installations from Res 1 to 6 and Com 1 to 6 as detailed per TCNA Environmental Classifications
- Excellent elongation and flexibility for use in both change-of-plane and joint applications in tile or stonework
- Can be used in pools and spas
- Helps to prevent mold and mildew

### Where to use:

- Interior/exterior residential and commercial installations from Res 1 to 6 and Com 1 to 6 per TCNA Environmental Classifications
- As a flexible barrier/filler between horizontal/vertical surfaces and any other changes of plane
- Expansion joints in non-traffic, normal-traffic and heavy-traffic areas
- Countertops, vanities, sinks, bathtubs, showers, steam rooms, pools, spas, backsplashes and fixtures

**Limitations:**

- Application temperature range is 40°F to 90°F (4°C to 32°C).
- Mapesil T may stain porous materials. Test a small area for staining or leaching before use to ensure compatibility with such porous materials as natural stone.
- Mapesil T should not be used in areas where material may come in contact with plasticizers or other materials that will prevent or diminish adhesion.
- Do not use Mapesil T for structural glazing.
- Not for use in expansion/movement joints with greater than 25% movement.
- For joints with depth greater than 1/2" (12 mm), the caulking depth must be controlled by a closed-cell backer rod.
- Joint widths should not exceed 1" (2,5 cm).
- Although Mapesil T is color-matched to MAPEI's grout color palette, expect a slight variation in color due to the difference in composition between materials.
- Not paintable; painting should be done before installation of Mapesil T.

**Product application:**

Read all installation instructions thoroughly before installation.

1. Caulking should take place after grout in the installation area has set.
2. For a clean, straight and neat sealant joint, mask both sides of the joint with masking tape.
3. Do not open the Mapesil T cartridge until preparatory work has been completed. Cut nozzle tip to the desired bead size at a 45-degree angle.
4. It will be necessary to insert a sharp tool (such as a screwdriver) inside the nozzle tip to puncture the protective aluminum foil seal inside the cartridge.
5. Apply Mapesil T with a caulking gun using steady, even pressure to completely bridge joints. Completely fill joints with sealant.
6. Tool the sealant using a "jointing tool" or the back of a spoon dipped in a solution of soapy water, to create a concave joint shape with a neat appearance.
7. Immediately after tooling the sealant, remove masking tape and wipe off any sealant from the face of the veneer with a paper towel before the material skins over. If the material skins over, excess sealant may need to be removed before curing with a commercial solvent.
8. Cured sealant will require mechanical means to remove.

**Protection:**

- Protect the installation area from traffic or water for at least 24 hours at 73°F (23°C).
- Note: Larger beads of caulk and cool, humid conditions will require a longer drying time.