

MAPEI Ultracolor Plus FA Grout

• manufacturer part# 25511 • gtin 093994255112

Rating: Not Rated Yet

Price

Sales price \$29.95

Tax amount

[Ask a question about this product](#)

Manufacturer [Mapei](#)

Description

Mapei Ultracolor Plus FA with DropEffect™ technology is an ultra premium, fine aggregate, fast-setting, polymer-modified, color-consistent, nonshrinking, efflorescence-free grout for joint widths from 1/16" to 3/4" (1.5 to 19 mm). DropEffect reduces surface absorption to help repel water, dirt and grime from penetrating grout joints. Ultracolor Plus FA is specially formulated with MAPEI's High-Hydrated Cement Technology (HCT™) to eliminate the common problems related to Portland-cement grout, such as color consistency and efflorescence. Along with offering higher polymer content, HCT reduces absorption and increases stain resistance when compared with standard-performance cement grouts. Ultracolor Plus FA is formulated with 10% recycled content.

Mapei Ultracolor Plus FA grout see [technical data sheet](#)

manufacturer part# 25511

color: #05 chamois

packaging 25 lbs. (11.3 kg) bag

click for [Mapei Ultracolor Plus FA grout color palette](#)

Features and benefits:

- Fine aggregate (FA) allows for narrow joint widths and improved cleanability
- No efflorescence (free of Portland cement)
- Easy to install and stain-resistant
- No sealer required

Where to use:

- Commercial and residential construction suitable for both interior and exterior installations
- For grouting dimensional stone, slate, granite, stone agglomerates and most types of ceramic, ceramic mosaic, quarry, brick paver, porcelain, glass and clay tiles
- When installing in submerged jobsites (swimming pools, spas, water features and fountains), allow 72 hours of curing
- For use where grout will be exposed to foot traffic within 3 to 4 hours

- For joint widths from 1/16" to 3/4" (1.5 to 19 mm)

Limitations:

- Sealing is not required. However, a high-performance penetrating grout sealer may still be applied from MAPEI's UltraCare™ family of sealers, which includes Penetrating Plus Stone, Tile & Grout Sealer; and Penetrating Plus SB Stone & Porcelain Tile Sealer. Follow the directions provided in the UltraCare Maintenance Guide.
- Do not use when a highly chemical-, impact- and stain-resistant grout is required or in heavy industrial tile installations. Instead, use an appropriate MAPEI epoxy grout (see the respective Technical Data Sheet [TDS] for details).
- When grouting in temperatures above 80°F (26°C), see the technical bulletin "Installing tile in hot weather" at www.mapei.com or consult MAPEI's Technical Services Department.

Shelf life and product characteristics before mixing:

- Shelf life: 1 year when stored in original, unopened packaging at 73°F (23°C) in a dry area
- Physical state: Powder