

## Mapei Keracolor S Silver 22725 Sanded Grout 25 lbs



mapei\_keracolor\_s\_silver\_25lbs.jpg



Mapei Keracolor S (silver grout) is a premium-grade, pre-blended, polymer-modified sanded Portland-cement tile grout that requires only the addition of water for mixing.

Rating: Not Rated Yet

**Price:**

Sales price: \$14.99

Tax amount: \$0.00

[Ask a question about this product](#)

Manufacturer: [Mapei](#)

### Description

**Mapei Keracolor S Silver Sanded Grout** see [technical data sheet](#)

manufacturer part# 22725 Silver

packaging: 25 lbs. (11,3 kg) paper bag

click for [Mapei Keracolor S grout color palette](#)

Mapei Keracolor S (silver grout) is a premium-grade, preblended, polymer-modified unsanded Portland-cement tile grout that requires only the addition of water for mixing. It will grout joints from 1/16" to 1/8" (1,5 to 3 mm).

### Features and benefits:

- For interior/exterior floors and walls
- Contains BioBlock™ technology for mold and mildew resistance

### Where to use:

- For grouting interior/exterior residential and commercial floor and wall surfaces in dry or wet conditions
- For grouting dimensional stone, slate, granite, stone agglomerates and most types of ceramic, ceramic mosaic, quarry, brick paver, porcelain, glass and clay tiles
- For joint widths from 1/16" to 1/8" (1,5 to 3 mm)
- For application in submerged conditions (swimming pools, spas, water features and fountains), once fully cured (after 21 days)

### Limitations:

- Do not install over substrates containing asbestos.

- Do not use to grout joints greater than 1/8" (3 mm) wide. Instead, use Keracolor S sanded grout or an appropriate MAPEI epoxy grout (see the respective Technical Data Sheet [TDS] for details).
- Do not use when a highly chemical-, impact- and stain-resistant grout is required or in heavy industrial tile installations. Instead, use an appropriate MAPEI epoxy grout (see the respective TDS for details).
- When grouting in temperatures above 80°F (26°C), see the Technical Bulletins at [www.mapei.com](http://www.mapei.com) or consult MAPEI's Technical Services Department.

**Shelf life and application properties:**

- Pot life: about 1 hour
- Compressive strength at 28 days: >3,500 psi (24,1 MPa)
- Shelf life: 2 years

**Reviews**

There are yet no reviews for this product.