

Mapei Keralastic Additive 5 gal

Mapei Keralastic is a second-generation “flexible” acrylic latex additive used to enhance the performance of Mapei Kerabond, which is a premium-grade dry-set mortar.

Rating: Not Rated Yet

Price

Sales price \$147.26

Tax amount

[Ask a question about this product](#)

Manufacturer [Mapei](#)

Description

Mapei Keralastic Adhesive see [technical data sheet](#)

Mapei Kerabond/Keralastic System is a high-performance, two-part system:

Keralastic™, a second-generation “flexible” acrylic latex additive, is used to enhance the performance of Kerabond™, which is a premium-grade dry-set mortar. This system has exceptional bond strength, flexural strength, elongation and freeze/thaw durability.

gtin 093994310682

manufacturer part# 7020020

packaging: 5 US gals. (18,9 L) plastic pail

available also in [2 gal. packaging](#)

Features and benefits:

- High-performance bond
- Best for most difficult tiles, substrates and conditions

Where to Use:

- Most interior/exterior residential and commercial installations on floors, walls and ceilings
- Installation of ceramic and porcelain tile, glass tile, quarry tile, pavers, Saltillo tile, and most types of marble, granite and natural stone

Limitations:

- Install only at temperatures between 40°F and 95°F (4°C and 35°C).
- Do not use for moisture-sensitive stone (green marble, some limestone and granite), agglomerate tiles or resin-backed tiles. Instead, use suitable epoxy or urethane adhesives (see respective Technical Data Sheet for more information).
- Some glass tile backings may not be suitable for use with Kerabond/Keralastic. Consult the recommendations of the TCNA and the glass tile manufacturer.

- For translucent or transparent glass tile, use white Granirapid ® or Adesilex™ P10.
- Use a white mortar when installing light-colored stones and translucent marble.
- Do not use over dimensionally unstable substrates such as hardwood flooring, oriented strand board (OSB), substrates containing asbestos, or metal. See "Suitable Substrates" section below.
- To use directly over gypsum-based patching or leveling substrates, apply suitable sealer before use. See MAPEI's Technical Bulletin 010506-TB, "Installing MAPEI Products over Gypsum."

Shelf Life and Application Properties* at 73°F (23°C) and 50% relative humidity:

- Shelf life 1 year (Kerabond); 2 years (Keralastic)
- Open time* 20 to 30 minutes
- Pot life* > 2 hours
- Time before grouting 24 hours
- VOCs (Rule #1168 of California's SCAQMD) 0 g/L

* Open time and pot life vary based on jobsite conditions.