

Mapei Keraply Latex Additive for Tile Mortar 2 gal

Mapei Keraply is a professional-grade, acrylic latex admixture used to enhance the performance of Keraset, Adesilex™ P10 and Keraflor™ dry-set mortars.

Rating: Not Rated Yet

Price

Sales price \$36.62

Tax amount

[Ask a question about this product](#)

Manufacturer [Mapei](#)

Description

Mapei Keraply Latex Additive for Tile Mortar see [technical data sheet](#)

gtin 093994307576

manufacturer part#: 7033010

packaging: 2 US gals. (7,57 L) plastic jug

Mapei Keraply is a professional-grade, acrylic latex admixture used to enhance the performance of dry-set mortars as well as Adesilex™ P10 glass tile mortar. This highly recommended admixture enhances bond strength, flexural strength, elongation and freeze/thaw durability.

Features and benefits:

- Improves bond strength of mortar
- Good for most difficult tiles and interior/exterior surfaces

Where to use:

- Interior/exterior residential and commercial installations
- Installation of ceramic and porcelain tile, quarry tile, pavers, Saltillo tile, and most types of marble, granite and natural stone

Limitations:

- Install only at temperatures between 40°F and 95°F (4°C and 35°C).
- Do not use for moisture-sensitive stone (green marble, some limestones and granites), agglomerate tiles, cultured marble or resin-backed tiles. Instead, use suitable epoxy or urethane adhesives (see respective Technical Data Sheet for more information).
- Use a white mortar when installing light-colored stones and translucent marble.
- Do not use over dimensionally unstable substrates such as hardwood flooring, oriented strand board (OSB), substrates containing asbestos, or metal.
- To use directly over gypsum-based patching or leveling substrates, apply suitable sealer before use. See MAPEI's Technical Bulletin

010506-TB, "Installing MAPEI Products over Gypsum."

Suitable Substrates:

- Concrete (cured at least 28 days)
- Masonry cement block, brick, cement mortar beds and leveling coats
- Cement backer units (CBU) – see manufacturer's installation guidelines
- APA and CANPLY Group 1 exterior-grade plywood (interior, residential and light commercial in dry conditions only)
- See the Technical Data Sheet of the mortar being used for a complete listing of suitable substrates.