

## Mapei Ultraflex 2 Gray Tile Mortar 50 lbs

Mapei Ultraflex 2 (gray) is a professional-grade, single-component, high-performance, polymer-modified thin-set mortar for interior and exterior installations of dimensional stone, ceramic, porcelain and quarry tile.

Rating: Not Rated Yet

**Price**

Sales price \$20.18

Tax amount

[Ask a question about this product](#)

Manufacturer [Mapei](#)

### Description

**Mapei Ultraflex 2 Gray Tile Mortar** see [technical data sheet](#)

gtin 093994115508

manufacturer part# 0060055

packaging: paper bag of 50 lbs. (22,7 kg)

color: gray

**available also in** [white color](#)

**Mapei Ultraflex 2** (gray) is a professional-grade, single-component, high-performance, polymer-modified thin-set mortar for interior and exterior installations of ceramic, porcelain and dimensional natural-stone tile. This mortar has a high content of unique dry polymer, resulting in excellent adhesion to the substrate and tile. Ultraflex 2 meets or exceeds ANSI A118.4 and ANSI A118.11 requirements when mixed with water. Ultraflex 2 can be used for interior and exterior installations of tile in most residential floor and wall applications. In commercial applications, use on interior floor and wall installations and exterior floors.

### Features and benefits:

- Polymer-enriched for high performance and deformability
- Smooth and creamy consistency for easy application

### Where to use:

- Most interior/exterior residential installations on floors and walls
- Most interior/exterior commercial installations on floors
- Most interior commercial installations on walls
- Installation of ceramic and porcelain tile, quarry tile, pavers, Saltillo tile, and many types of marble, granite and natural stone

### Limitations:

- Install only at temperatures between 40°F and 95°F (4°C and 35°C).
- Do not use for moisture-sensitive stone (green marble, some limestones and granites), agglomerate tiles or resin-backed tiles. Instead, use a suitable epoxy or urethane adhesive. See the respective Technical Data Sheet for more information.
- Do not use over dimensionally unstable substrates such as hardwood flooring, oriented strand board (OSB), substrates containing asbestos, or metal. See the "Suitable Substrates" section.
- To use directly over gypsum-based patching or leveling substrates, apply suitable primer before use. See MAPEI Technical Bulletin 010313-TB, "Gypsum-Based Floors and Walls: Which MAPEI Products Can Be Applied?".