

TECHNICAL DATA SHEET

SYNTEKO RETARDER 1670

Synteko Retarder 1670 is intended to be added to the final coat of Synteko Classic 1636 Matte 35, 1637 Semi Gloss 50 or 1646 Gloss 90 when large open floor areas need to be coated with Synteko Classic, or when the conditions are very warm and/or dry (low Relative Humidity). Addition of Synteko Retarder will help to improve the open time, flow and leveling of Synteko Classic under these challenging conditions.

DIRECTIONS FOR USE

The catalyzed Synteko Classic mixture may be diluted with up to 10% with Synteko Retarder. The amount added depends on the jobsite conditions, e.g. airflow, layout and/or size of the floor to be coated. First, mix Synteko Classic with the proper amount of Synteko Hardener as recommended on the Technical Data Sheet for Synteko Classic. Next, add up to 10% Synteko Retarder to the catalyzed Synteko Classic mixture and mix thoroughly. Allow this mixture to stand for 5-10 minutes before use.

TECHNICAL DATA

Description and color: Clear, low viscosity, water white liquid solvent mixture

Density: 7.67 lb/gal US

VOC: 918 g/l

Flashpoint: 64°F

Shelf life: 24 months in closed container

SAFETY PRECAUTIONS

Contains: Proprietary blend of Alcohols and Dibasic Esters.

Fire classification: Highly flammable, Irritating to skin, eyes, and respiratory system. Keep container closed in well ventilated place. Do not eat, drink or smoke during use. Wear suitable gloves and respiratory protection. Do not empty into drains. Take precautionary measures against static discharges. **Keep out of reach of children.** Refer to MSDS sheet for further information.

DISCLAIMER: Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us. Date 07/08